

# ICC-ES PMG Product Certificate



## PMG-1358

Effective Date: October 2022

This listing is subject to re-examination in one year.



[www.icc-es-pmg.org](http://www.icc-es-pmg.org) | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 22 00 00—PLUMBING  
Section: 22 40 00—Facility Water Distribution  
Section: 22 09 00—Instrumentation and Control for Plumbing

### Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system.

Product: Water Temperature Limiting Device

Listee: CALEFFI North America, Inc.  
3883 W. Milwaukee Road  
Milwaukee, WI 53208  
[www.caleffi.us](http://www.caleffi.us)

### Compliance with the following codes:

2021, 2018, 2015, 2012 and 2009 *International Plumbing Code*® (IPC)  
2021, 2018, 2015, 2012 and 2009 *International Residential Code*® (IRC)  
2021, 2018, 2015, 2012 and 2009 *Uniform Plumbing Code*® (UPC)\*  
2020, 2015, 2010 and 2005 *National Plumbing Code of Canada*® (NPC)\*\*  
\* Copyrighted publication of the International Association of Plumbing and Mechanical Officials  
\*\* Copyrighted publication of National Research Council Canada

### Compliance with the following standards:

ASSE 1070/ASME A112.1070/CSA B125.70-2020 Performance Requirements for Water Temperature Limiting Devices  
CSA B125.3-2012, Plumbing Fittings

### Identification:

Each device shall have the following information marked on it and all markings shall be visible after installation:

- The manufacturer's recognized name, trademark, or other mark; or
- Model number
- Hot and cold indications on inlets.
- The ICC-ES PMG listing mark

The device shall have markings to indicate the hot and cold-water inlet ports and that indicate the direction or means to change the outlet temperature setting. Markings shall be clear, permanent and visible after installation.

### Installation:

*Listings are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the listing or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this listing, or as to any product covered by the listing.*

Plumbing Supply fittings shall be installed in accordance with the manufacturer's instructions and the applicable codes.

Models:

| Model No. | Description                                |
|-----------|--------------------------------------------|
| 521201A   | 3/8", Anti-scald thermostatic mixing valve |
| 521201AP  | 3/8" compression union, plug/fittings      |
| 521342A   | 1/2" NPTF                                  |
| 521347A   | 1/2" PEX crimp*                            |
| 521348A   | 1/2" PEX expansion**                       |
| 521349A   | 1/2" solder                                |
| 521352A   | 3/4" NPTF                                  |
| 521357A   | 3/4" PEX crimp*                            |
| 521358A   | 3/4" PEX expansion**                       |
| 521359A   | 3/4" solder                                |
| 521362A   | 1" NPTF                                    |
| 521367A   | 1" PEX crimp*                              |
| 521368A   | 1" PEX expansion**                         |
| 521369A   | 1" solder                                  |

\*PEX crimp end connection complies with ASTM F1807

\*\*PEX expansion end connection complies with ASTM F1960

Conditions of listing:

1. The CALEFFI's products recognized in this listing must be installed in accordance with the manufacturer's published installation instructions and the applicable codes.
2. The CALEFFI's products recognized in this listing are manufactured under a quality control program with annual surveillance inspections by ICC-ES.