EXPANSION GROUPS FOR HOT WATER STORAGE HEATERS **528 SERIES**





FUNCTION AND FEATURES

These are used in domestic water systems to protect the hot water storage heaters.	The shut-off valve upstream makes it possible to control the check valve.
Engineered with a compact design for easy installation and maintenance.	Thanks to its patented design, the shut-off valve downstream allows maintenance to the check valve while keeping active all the functionalities of the expansion relief valve.
Prevents dangerous backflows of hot water towards the hydraulic circuit.	Supplied complete with pre-formed shell insulation to guarantee perfect thermal insulation.

PRODUCT RANGE - 528 SERIES




CODE	SIZES	SETTING	CODE	SIZES	SETTING	
528 046	DN 15 1/2"	6 bar	528 156	DN 20 3/4"	6 bar	
528 048	DN 15 1/2"	8 bar	528 158	DN 20 3/4"	8 bar	
528 041	DN 15 1/2"	10 bar	528 151	DN 20 3/4"	10 bar	
528 056	DN 15 3/4"	6 bar	528 166	DN 20 1"	6 bar	
528 058	DN 15 3/4"	8 bar	528 168	DN 20 1"	8 bar	
528 051	DN 15 3/4"	10 bar	528 161	DN 20 1"	10 bar	

PERFORMANCE				
MAX. WORKING PRESSURE	10 bar			
MAX. WORKING TEMPERATURE	40°C			
DRAIN SIZE	40 mm			

BODY	DN 15		DN 20	
CONNECTIONS	1/2"	3/4"	3/4"	1"
MAX. VOLUME OF DOMESTIC HOT WATER STORAGE	200		1000 I	
HEATING POWER SUPPLIED TO THE STORAGE	max. 75 kW		max. 150 kW	

INSTALLATION DIAGRAM





WE RESERVE THE RIGHT TO CHANGE OUR PRODUCTS AND THEIR RELEVANT TECHNICAL DATA, CONTAINED IN THIS PUBLICATION, AT ANY TIME AND WITHOUT PRIOR NOTICE. Caleffi S.p.A. S.R. 229 n. 25 · 28010 Fontaneto d'Agogna (NO) · Italy Tel. +39 0322 8491 · Fax +39 0322 863723 info@caleffi.com · www.caleffi.com · © Copyright 2013 Caleffi