





PRODUCT FEATURES

- Compact and multi-function design:

 Award winning AngleMix[™] with cold water cross and outlet temperature gauge. Easy to install with adjustable pivot fittings.
- Stable mixing at low flows:

 Consistent mixed outlet water temperature down to 0.5 GPM to meet the demands of today's low flow plumbing fixtures.
- Posi-Stop™ Unions:

 Time saving installation and easy serviceability.

 Product integrated O-rings provide a field proven seal connection. Union tailpieces available in NPT male, press and sweat.

- Connection flexibility with pivot fittings: Adjustable pivot fittings allow for connection to water heater nipples up to 8½" spacing.
- **Tight hot water close-off:**Prevents recirculation temperature creep and droop during periods of non-use.
- Integral recirculation return port:

 No extra fittings needed. The cold water cross features a ½" FNPT port for hot water recirculation.

Trusted mixing, versatile pivot connection

Provides tempered water control for combi boilers, electric water heaters, and heat pump water heaters. The PivotMixer includes the award winning AngleMix, outlet temperature gauge, cold water cross with recirculation port and two adjustable pivot fittings. AngleMix complies with standards ASSE 1017, CSA B125.3, NSF/ANSI/CAN 372 and codes IPC, IRC, UPC, NPC. Certified by ICC-ES.

PRODUCT RANGE - PivotMixer™




| SYSTEM CONNECTION OPTION | CODE | |
|--|----------|--|
| ¾" NPT male | 520510AP | |
| ¾" press | 520516AP | |
| ¾" sweat | 520519AP | |
| Connection to water heating appliance is ¾" union NPT female | | |


PERFORMANCE

| MAX. WORKING PRESSURE | 150 psi |
|--|--------------------------|
| ADJUSTMENT TEMPERATURE RANGE | 95 — 150 °F (35 — 66 °C) |
| MINIMUM FLOW FOR OPTIMUM PERFORMANCE: (WITH RECIRCULATION) | 0.5 GPM (0 GPM) |

APPLICATION DIAGRAMS



CONSTRUCTION



Caleffi Partner:





Caleffi North America, Inc. sales@caleffi.com · www.caleffi.com © Copyright 2024 Caleffi North America, Inc.