

Perdite di carico continue TUBI IN PE 100 - PN 16 - Temperatura acqua = 10°C

r = perdite di carico continue, mm c.a./m																G = portate, l/h		v = velocità, m/s	
r	\varnothing_e	20	25	32	40	50	63	75	90	110	125	140	160	180	200	\varnothing_e	r		
	\varnothing_i	16	20,4	26	32,6	40,8	51,4	61,4	73,6	90	102,2	114,6	130,8	147,2	163,6	\varnothing_i			
2	G	79	154	297	548	1.008	1.887	3.058	5.001	8.633	12.190	16.634	23.815	32.817	43.714	G	2		
	v	0,11	0,13	0,16	0,18	0,21	0,25	0,29	0,33	0,38	0,41	0,45	0,49	0,54	0,58	v			
4	G	118	228	441	815	1.498	2.804	4.544	7.431	12.828	18.114	24.718	35.390	48.766	64.959	G	4		
	v	0,16	0,19	0,23	0,27	0,32	0,38	0,43	0,49	0,56	0,61	0,67	0,73	0,80	0,86	v			
6	G	149	288	556	1.027	1.889	3.536	5.728	9.368	16.173	22.837	31.163	44.617	61.481	81.896	G	6		
	v	0,21	0,24	0,29	0,34	0,40	0,47	0,54	0,61	0,71	0,77	0,84	0,92	1,00	1,08	v			
8	G	175	339	655	1.211	2.226	4.167	6.752	11.042	19.063	26.918	36.731	52.589	72.466	96.528	G	8		
	v	0,24	0,29	0,34	0,40	0,47	0,56	0,63	0,72	0,83	0,91	0,99	1,09	1,18	1,28	v			
10	G	199	385	744	1.376	2.529	4.734	7.670	12.544	21.655	30.578	41.726	59.741	82.321	109.656	G	10		
	v	0,28	0,33	0,39	0,46	0,54	0,63	0,72	0,82	0,95	1,04	1,12	1,23	1,34	1,45	v			
12	G	221	428	826	1.527	2.807	5.254	8.512	13.921	24.033	33.936	46.308	66.300	91.361	121.697	G	12		
	v	0,31	0,36	0,43	0,51	0,60	0,70	0,80	0,91	1,05	1,15	1,25	1,37	1,49	1,61	v			
14	G	242	467	902	1.667	3.065	5.738	9.296	15.203	26.246	37.061	50.572	72.405	99.773	132.903	G	14		
	v	0,33	0,40	0,47	0,55	0,65	0,77	0,87	0,99	1,15	1,25	1,36	1,50	1,63	1,76	v			
16	G	261	504	974	1.799	3.308	6.193	10.033	16.409	28.327	40.000	54.582	78.146	107.684	143.440	G	16		
	v	0,36	0,43	0,51	0,60	0,70	0,83	0,94	1,07	1,24	1,35	1,47	1,62	1,76	1,90	v			
18	G	279	539	1.042	1.925	3.539	6.624	10.732	17.551	30.299	42.784	58.382	83.587	115.181	153.427	G	18		
	v	0,39	0,46	0,54	0,64	0,75	0,89	1,01	1,15	1,32	1,45	1,57	1,73	1,88	2,03	v			
20	G	296	573	1.106	2.044	3.758	7.035	11.397	18.640	32.180	45.439	62.005	88.774	122.329	162.948	G	20		
	v	0,41	0,49	0,58	0,68	0,80	0,94	1,07	1,22	1,41	1,54	1,67	1,84	2,00	2,15	v			
22	G	313	605	1.168	2.159	3.969	7.429	12.035	19.683	33.981	47.983	65.475	93.743	129.176	172.069	G	22		
	v	0,43	0,51	0,61	0,72	0,84	0,99	1,13	1,29	1,48	1,62	1,76	1,94	2,11	2,27	v			
24	G	329	636	1.228	2.269	4.171	7.807	12.649	20.687	35.713	50.429	68.813	98.522	135.761	180.840	G	24		
	v	0,45	0,54	0,64	0,75	0,89	1,05	1,19	1,35	1,56	1,71	1,85	2,04	2,22	2,39	v			
26	G	344	665	1.285	2.375	4.366	8.173	13.241	21.655	37.384	52.789	72.033	103.133	142.115	189.304	G	26		
	v	0,48	0,57	0,67	0,79	0,93	1,09	1,24	1,41	1,63	1,79	1,94	2,13	2,32	2,50	v			
28	G	359	694	1.341	2.478	4.555	8.526	13.814	22.592	39.002	55.072	75.149	107.594	148.263	197.492	G	28		
	v	0,50	0,59	0,70	0,82	0,97	1,14	1,30	1,48	1,70	1,86	2,02	2,22	2,42	2,61	v			
30	G	373	722	1.395	2.577	4.738	8.869	14.369	23.500	40.570	57.287	78.171	111.921	154.224	205.434	G	30		
	v	0,52	0,61	0,73	0,86	1,01	1,19	1,35	1,53	1,77	1,94	2,11	2,31	2,52	2,71	v			
35	G	408	788	1.523	2.814	5.175	9.686	15.692	25.664	44.306	62.562	85.370	122.227	168.426	224.351	G	35		
	v	0,56	0,67	0,80	0,94	1,10	1,30	1,47	1,68	1,93	2,12	2,30	2,53	2,75	2,96	v			
40	G	440	851	1.644	3.038	5.585	10.454	16.937	27.699	47.819	67.523	92.138	131.918	181.780	242.140	G	40		
	v	0,61	0,72	0,86	1,01	1,19	1,40	1,59	1,81	2,09	2,29	2,48	2,73	2,97	3,20	v			
45	G	471	910	1.758	3.249	5.974	11.181	18.116	29.628	51.148	72.224	98.553	141.102	194.436	258.998	G	45		
	v	0,65	0,77	0,92	1,08	1,27	1,50	1,70	1,93	2,23	2,45	2,65	2,92	3,17	3,42	v			
50	G	500	967	1.867	3.451	6.344	11.875	19.240	31.466	54.322	76.706	104.669	149.858	206.502	275.070	G	50		
	v	0,69	0,82	0,98	1,15	1,35	1,59	1,80	2,05	2,37	2,60	2,82	3,10	3,37	3,63	v			
60	G	555	1.073	2.072	3.830	7.041	13.179	21.353	34.921	60.287	85.128	116.162	166.313	229.177	305.274	G	60		
	v	0,77	0,91	1,08	1,27	1,50	1,76	2,00	2,28	2,63	2,88	3,13	3,44	3,74	4,03	v			
70	G	606	1.172	2.263	4.182	7.689	14.393	23.319	38.137	65.838	92.967	126.859	181.628	250.280	333.384	G	70		
	v	0,84	1,00	1,18	1,39	1,63	1,93	2,19	2,49	2,87	3,15	3,42	3,75	4,09	4,41	v			
80	G	654	1.265	2.443	4.514	8.299	15.534	25.168	41.161	71.058	100.338	136.917	196.029	270.124	359.818	G	80		
	v	0,90	1,07	1,28	1,50	1,76	2,08	2,36	2,69	3,10	3,40	3,69	4,05	4,41	4,75	v			
90	G	700	1.353	2.613	4.828	8.877	16.616	26.920	44.026	76.006	107.324	146.450	209.677	288.931	384.869	G	90		
	v	0,97	1,15	1,37	1,61	1,89	2,22	2,53	2,87	3,32	3,63	3,94	4,33	4,72	5,09	v			
100	G	743	1.437	2.775	5.128	9.428	17.647	28.590	46.758	80.722	113.984	155.538	222.689	306.861	408.752	G	100		
	v	1,03	1,22	1,45	1,71	2,00	2,36	2,68	3,05	3,52	3,86	4,19	4,60	5,01	5,40	v			

Se = superficie esterna, m ² /m																Si = sezione interna, mm ²		V = contenuto acqua, l/m	
\varnothing_e [mm]	20	25	32	40	50	63	75	90	110	125	140	160	180	200	\varnothing_e [mm]				
\varnothing_i [mm]	16	20,4	26	32,6	40,8	51,4	61,4	73,6	90	102,2	114,6	130,8	147,2	163,6	\varnothing_i [mm]				
Se [m ² /m]	0,063	0,079	0,101	0,126	0,157	0,198	0,236	0,283	0,346	0,393	0,440	0,503	0,565	0,628	Se [m ² /m]				
Si [mm ²]	201	327	531	835	1.307	2.075	2.961	4.254	6.362	8.203	10.315	13.437	17.018	21.021	Si [mm ²]				
V [l/m]	0,20	0,33	0,53	0,83	1,31	2,07	2,96	4,25	6,36	8,20	10,31	13,44	17,02	21,02	V [l/m]				